

# TECHNICAL SHEET

valid from 1.2.2012

review .....

<b>PRODUCT NAME:</b>	<b>PERFORMER 45/140</b>
<b>APPLICATION:</b>	<b>FOOTBALL</b>
<b>MATERIAL:</b>	<b>PILE:</b> PE monofilament (profile great lens)
	<b>PRIMARY BACKING:</b> 100% PP
	<b>SECONDARY BACKING:</b> SBR Latex
<b>GAUGE:</b>	3/4"
<b>COLOR:</b>	bicolor green

PROPERTIES	UNIT	TYPICAL VALUE	TOLERATION
Pile fineness	[dtex]	16.000/8	± 5%
Pile width	[mm]	1,3	± 10%
Pile thickness	[µm]	280	± 10%
Pile weight per unit area	[g/m <sup>2</sup> ]	1.193	± 10%
Stitch rate per 10 cm (length)	[-/ 10 cm]	14	± 1
Number of tufts/ m <sup>2</sup>	[-/m <sup>2</sup> ]	7.349	± 5%
Number of piles/ m <sup>2</sup>	[-/m <sup>2</sup> ]	117.584	± 5%
Pile height	[mm]	45	± 10%
Weight primary backing	[g/m <sup>2</sup> ]	254	± 10%
Weight secondary backing	[g/m <sup>2</sup> ]	1000	± 10%
Total weight	[g/m <sup>2</sup> ]	2.447	± 10%
Turf withdrawal force	[N]	> 30	
UV stabilisation ( QUV – lamp A)	[h]	3.000	
Color fastness – gray scale	Scale	≥ 4	
Stand. roll width	[m]	4,04	± 0,02

## COMMENTS:

Any supplementary information and certificates are available upon request at our sales department.  
According to the Directive 76/ 769 this product does not contain any dangerous substances.