

TECHNICAL SHEET

valid from 1.2.2012

review

PRODUCT NAME:	PERFORMER 60/165
APPLICATION:	FOOTBALL
MATERIAL:	PILE: PE monofilament (profile great lens)
	PRIMARY BACKING: 100% PP
	SECONDARY BACKING: SBR Latex
GAUGE:	3/4"
COLOR:	bicolor green

PROPERTIES	UNIT	TYPICAL VALUE	TOLERATION
Pile fineness	[dtex]	16.000/8	± 5%
Pile width	[mm]	1,3	± 10%
Pile thickness	[µm]	280	± 10%
Pile weight per unit area	[g/m ²]	1.807	± 10%
Stitch rate per 10 cm (length)	[-/ 10 cm]	16,5	± 1
Number of tufts/ m ²	[-/m ²]	8.661	± 5%
Number of piles/ m ²	[-/m ²]	138.576	± 5%
Pile height	[mm]	60	± 10%
Weight primary backing	[g/m ²]	254	± 10%
Weight secondary backing	[g/m ²]	950	± 10%
Total weight	[g/m ²]	3.011	± 10%
Turf withdrawal force	[N]	> 30	
UV stabilisation (QUV – lamp A)	[h]	3.000	
Color fastness – gray scale	Scale	≥ 4	
Stand. roll width	[m]	4,04	± 0,02

COMMENTS:

Any supplementary information and certificates are available upon request at our sales department.
According to the Directive 76/ 769 this product does not contain any dangerous substances.