

# TECHNICAL SHEET

valid from 1.1.2012

review .....

<b>PRODUCT NAME:</b>	<b>PLAY COMFORT S</b>	
<b>APPLICATION:</b>	<b>MULTISPORT</b>	
<b>MATERIAL:</b>	<b>PILE:</b>	PE monofilament (texturized)
	<b>PRIMARY BACKING:</b>	100% PP
	<b>SECONDARY BACKING:</b>	SBR Latex
<b>GAUGE:</b>	3/8"	
<b>COLOR:</b>	green, blue	

PROPERTIES	UNIT	TYPICAL VALUE	TOLERATION
Pile fineness	[dtex]	11.500/8	± 5%
Pile width	[mm]	1	± 10%
Pile thickness	[µm]	180	± 10%
Pile weight per unit area	[g/m <sup>2</sup> ]	1.427	± 10%
Stitch rate per 10 cm (length)	[-/ 10 cm]	21,5	± 1
Number of tufts/ m <sup>2</sup>	[-/m <sup>2</sup> ]	22.572	± 5%
Number of piles/ m <sup>2</sup>	[-/m <sup>2</sup> ]	361.152	± 5%
Pile height	[mm]	24	± 10%
Weight primary backing	[g/m <sup>2</sup> ]	254	± 10%
Weight secondary backing	[g/m <sup>2</sup> ]	950	± 10%
Total weight	[g/m <sup>2</sup> ]	2.631	± 10%
Turf withdrawal force	[N]	> 30	
UV stabilisation (QUV – lamp A)	[h]	3.000	
Color fastness – gray scale	Scale	≥ 4	
Stand. roll width	[m]	4,02	± 0,02

## COMMENTS:

**Recommended infill:** quartz sand 0,6 - 1,2 mm -> ± 11 kg/m<sup>2</sup>

Any supplementary information and certificates are available upon request at our sales department.  
According to the Directive 76/ 769 this product does not contain any dangerous substances.



Juta a.s., Dukelská 417 | www.juta.cz  
544 15 Dvůr Králové nad Labem,  
Česká republika  
e-mail: jutagrass@juta.cz  
Fax +420 499 314 572

JUTAggrass Česká republika  
Na Borkách 89  
Dvůr Králové nad Labem  
Telefon: +420 499 314 567  
+420 499 314 575